

## POOL FENCE SAFETY CHECKLIST

Check the safety of your pool fence with these four easy steps.

Regular inspections of your pool fence are necessary to ensure unaccompanied young children do not gain access to the pool area. If you're unable to check off all items below ARC Fences recommends arranging for its immediate repair, replacement or removal.

1	Check the pool fence prevents small children from entering the pool
	Pool fence is at least 1200mm high from a solid ground surface at any point
	Space between the highest lower horizontal rails and the lowest upper horizontal rails is a minimum of 900mm
	Boundary fence is at least 1800mm from a solid ground surface at any point
	Gap under the fence is not more than 100mm from the ground
	Spacing between vertical rails is not more than 100mm
	There are no sharp edges, sharp projections, entrapping spaces or similar hazards along the fence
2	Check the pool gate
	Swings outwards only (away from the pool)
	Swings outwards only (away from the pool)
	Swings outwards only (away from the pool)  Gap under the gate is not more than 100mm from the ground  Is fitted with a self-closing device and will self-close and latch from
	Swings outwards only (away from the pool)  Gap under the gate is not more than 100mm from the ground  Is fitted with a self-closing device and will self-close and latch from any position
	Swings outwards only (away from the pool)  Gap under the gate is not more than 100mm from the ground  Is fitted with a self-closing device and will self-close and latch from any position  Cannot be locked in an open position
	Swings outwards only (away from the pool)  Gap under the gate is not more than 100mm from the ground  Is fitted with a self-closing device and will self-close and latch from any position  Cannot be locked in an open position  Gap between the latching side of gate and post is not more than 10mm  Latch is a minimum of 1500mm above the ground and 1400mm above
	Swings outwards only (away from the pool)  Gap under the gate is not more than 100mm from the ground  Is fitted with a self-closing device and will self-close and latch from any position  Cannot be locked in an open position  Gap between the latching side of gate and post is not more than 10mm  Latch is a minimum of 1500mm above the ground and 1400mm above the highest lower horizontal rail  If latch release is lower than 1500mm:  Appropriate shielding is required
	Swings outwards only (away from the pool)  Gap under the gate is not more than 100mm from the ground  Is fitted with a self-closing device and will self-close and latch from any position  Cannot be locked in an open position  Gap between the latching side of gate and post is not more than 10mm  Latch is a minimum of 1500mm above the ground and 1400mm above the highest lower horizontal rail  If latch release is lower than 1500mm:

3	Fences and gates must be in good condition to be effective
	All fixtures and fittings are tight and secure
	Posts and gates are solid and free from excessive corrosion
	Footings and posts are firm in the ground and not removable
	Welds on panels are secure, unbroken and free from corrosion
4	Pool surroundings
	Chemicals, chairs and toys are stored in a safe area away from the pool
	Clothes lines, barbeques, trees or shrubs are away from fencing
	A resuscitation sign is displayed in the immediate vicinity of the pool area

## Since 1920, ARC Fences has been committed to the safety of families around Australia.

The information in this checklist has been developed from Australian Standard 1926.1-2007. This checklist is a guide to pool fencing only.

All homeowners should also download a complete checklist on pool safety from Royal Life Saving at www.homepoolsafety.com.au.

To guarantee your fence is fully compliant please refer to your local council.



FOR MORE INFORMATION ON ARC FENCES PRODUCTS CALL US OR VISIT OUR WEBSITE

arcfences.com.au 1800 FENCES 336237

